

fMRI Course, Day 8:  
Design Optimization and  
2<sup>nd</sup>-Level Analysis  
August 7<sup>th</sup>, 2023

# Overview of PSY808 Course

**Questions from previous lecture?**

# How did the lab go?

Did the contrasts make sense?

What was the most confusing part of the lab?

Questions:



1. How to increase the size of the t-statistic?
2. How to deal with low-frequency noise?
3. Should we lowpass filter fMRI data?





# Slides from Yesterday



# Applying the GLM to fMRI Data



# Applying the GLM to fMRI Data



## Applying the GLM to fMRI Data

**Drawback: Very tedious to implement without scripting!**

**For AFNI users: Can use 'IM' basis function in 3dDeconvolve**

# Parametric Modulation: Other Considerations

Orthogonalizing the regressors as part of the design

Orthogonalizing as part of the GLM



## Module List

fMRI model specification &lt;-X

## Current Module: fMRI model specification

.... Time Modulation	No Time Modulation
.... Parametric Modulations	
..... Parameter	
..... Name	<-X
..... Values	<-X
..... Polynomial Expansion	<-X
..... Parameter	
..... Name	<-X
..... Values	<-X
..... Polynomial Expansion	<-X
.... Orthogonalise modulations	Yes
.. Multiple conditions	
.. Regressors	
.. Multiple regressors	
.. High-pass filter	128
Factorial design	
Basis Functions	
. Canonical HRF	
.. Model derivatives	No derivatives
Model Interactions (Volterra)	Do not model Interactions
Global normalisation	None

## Current Item: Orthogonalise modulations

\*Yes  
No

Specify...

## Orthogonalise modulations

Orthogonalise regressors within trial types.

One of the following options must be selected:

\* Yes



\* No

Should be set  
to "No"





# Why?



Low collinearity  
ISI=3s



High collinearity  
ISI=1s




Feedback  
orthogonalized  
with respect to  
Stimulus






# Why?

Regressors without orthogonalization




Correct orthogonalization for interpretable Unmodulated




**RT** wrt **Unmod**  
**Intensity** wrt **Unmod**

SPM  
RT first  
Intensity second



**RT** wrt **Unmod**  
**Intensity** wrt **Unmod** and **RT**

SPM  
Intensity first  
RT second



**RT** wrt **Unmod** and **Intensity**  
**Intensity** wrt **Unmod**

# Demonstration of Parametric Modeling Setup

# Other Experimental Modeling Options

**Parametric Modulation**

**Finite Impulse Response (FIR)**


# Other Experimental Modeling Options

**Parametric Modulation**

**Finite Impulse Response (FIR)**

# Finite Impulse Response (FIR)

Basis functions such as the HRF assume a stereotypical shape



Source: [mri-q.com](http://mri-q.com)

# Finite Impulse Response (FIR)

**But what if we don't want to assume a shape?**


**Example: You want to see whether the peak for condition A is later than the peak for condition B**

**Another example: You think the overall shape of the BOLD response is different between patients and controls, even though the amplitude is the same**



# Finite Impulse Response (FIR)

You specify the window length and number of timepoints

e.g.: 20s window, 10 timepoints




# Finite Impulse Response (FIR)






# Finite Impulse Response (FIR)



# Finite Impulse Response (FIR)



# Demonstration of FIR Modeling Setup



## **ImCalc: The Image Calculator**

**One of the most versatile tools is the image calculator**



**Every package has one (AFNI, FSL, MRtrix, etc.)**

**Simple to do basic arithmetic on a 3D image**


# ImCalc: The Image Calculator



# ImCalc: The Image Calculator



# ImCalc: The Image Calculator



SPM12 (7771): Graphics

File Edit View Insert Tools Desktop Window SPM Figure Help

mm: 0.0 30.0 30.0  
vx: 27.0 48.3 34.3  
Intensity: 0.000696186


File: `./1stLevel/beta_0001.nii`  
Dimensions: 53 x 63 x 52  
Datatype: float32  
Intensity: Y = 1 X  
spm\_spm:beta (0001) - Sn(1) Inc\*bf(1)

Vox size: -3 x 3 x 3  
Origin: 27 38.3 24.3  
Dir Cos: 1.000 0.000 0.000  
0.000 1.000 0.000  
0.000 0.000 1.000

Full Volume  Hide Crosshair   
World Space  Trilinear interp.   
Auto Window  Add Overlay...

right {mm} 0  
forward {mm} 0  
up {mm} 0  
pitch {rad} 0  
roll {rad} 0  
yaw {rad} 0  
resize {x} 1  
resize {y} 1  
resize {z} 1

Set Origin Reorient...



SPM12 (7771): Graphics

File Edit View Insert Tools Desktop Window SPM Figure Help

mm: 0.0 30.0 30.0  
vx: 27.0 48.3 34.3  
Intensity: -0.37464

File: `./1stLevel/beta_0002.nii`  
Dimensions: 53 x 63 x 52  
Datatype: float32  
Intensity: Y = 1 X  
spm\_spm:beta (0002) - Sn(1) Con\*bf(1)


Vox size: -3 x 3 x 3  
Origin: 27 38.3 24.3  
Dir Cos: 1.000 0.000 0.000  
0.000 1.000 0.000  
0.000 0.000 1.000

Full Volume  Hide Crosshair   
World Space  Trilinear interp.   
Auto Window  Add Overlay...

right {mm} 0  
forward {mm} 0  
up {mm} 0  
pitch {rad} 0  
roll {rad} 0  
yaw {rad} 0  
resize {x} 1  
resize {y} 1  
resize {z} 1

Set Origin Reorient...

# ImCalc: The Image Calculator





# Today's Lecture

**Design optimization and power analysis**

**OptimizeX and optseq (optimization), Gpower (power analysis)**

**Group-level analysis options**



**Other Statistical Scenarios**

# Review So Far

From stimulus to the BOLD response

How tissue properties, blood flow, and magnetic properties interact

Creating contrast images from T1- and T2-weightings



# **Preprocessing Steps**

**Brain extraction (or “skull stripping”)**

**Motion Correction**

**Slice Timing Correction**

**Smoothing**

**Registration**

**Normalization**


**Temporal Filtering**

# **Review So Far**

**Overview of the General Linear Model**

**Parameter Estimates**

**Creating beta maps and contrast maps**




**Fit at each voxel (“mass univariate” approach)**

# Questions

**Let's look at some GLMs, and see if you can identify each part!**



ming Smooth  
 lise Segment  
 ation  
 Review  
 Estimate  
 S  
 al Modelling  
 tional MRI  
 Render..... FMRI  
 ImCalc DICOM Imp...  
 Defaults Quit  
 3, 2005-2009

SPM5: spm\_fmri\_spm\_  
 =====  
 Mapping files  
 Calculating globals  
 ...



ultis\_2  
 ultis\_2/


### Statistical analysis: Design



#### Design description...

Basis functions : hrf  
 Number of sessions : 2  
 Trials per session : 2 2  
 Interscan interval : 2.00 [s]  
 High pass Filter : [min] Cutoff: 128 [s]  
 Global calculation : mean voxel value  
 Grand mean scaling : session specific  
 Global normalisation : None






# **Review: SPM Terms for Analysis**

**1<sup>st</sup>-Level Analysis: Individual subject (all trials across runs)**

**2<sup>nd</sup>-Level Analysis: Group-Level Analysis  
(all subjects within the experiment)**

# Review of Collinearity

Last week, we looked at a correlation matrix



SPM12 (7771): Menu

Realign (E... ▾) Slice timing Smooth

Coregiste... ▾ Normalise... ▾ Segment

Select your SPM.mat file

Specify 1st-level Review

Specify 2nd-level Estimate

Results

Dynamic Causal Modelling

SPM for functional MRI



Display Check Reg Render... ▾ FMRI ▾

Toolbox: ▾ PPis ImCalc DICOM Import

Help Utils... ▾ Batch Quit

Design

### Statistical analysis: Design orthogonality



Measure : abs. value of cosine of angle between columns of design matrix  
 Scale : black - colinear (cos=+1/-1)  
 white - orthogonal (cos=0)  
 gray - not orthogonal or colinear

```

67
68 %% Decide whether you want to see the searchlight/ROI/... during
69 cfg.plot_selected_voxels = 500; % 0: no plotting, 1: every step
70
71 %% Add additional output measures if you like
72 % See help decoding_transform_results for possible measures
73
74 % cfg.results.output = {'accuracy_minus_chance', 'AUC'}; % 'acc
75
76 % You can also use all methods that start with "transres_", e.g
77 %   cfg.results.output = {'SVM_pattern'};
78 % will use the function transres_SVM_pattern.m to get the patte
79 % linear svm weights (see Haufe et al, 2015, Neuroimage)
80
81 %% Nothing needs to be changed below for a standard leave-one-r
82 %% validation analysis.
83
84 % The following function extracts all beta names and correspond
85 % numbers from the SPM.mat
86 regressor_names = design_from_spm(['/Users/ajahn/Downloads/fmri
87
88 % Extract all information for the cfg.files structure (labels w
89 cfg = decoding_describe_data(cfg,labelnames,labels,regressor_na
90
91 % This creates the leave-one-run-out cross validation design:
92 cfa_design = make_design_cv(cfg):

```


Command Window

```
ans =
```

1.0000	-0.0925	0	0	0.4635	0
-0.0925	1.0000	0	0	0.4625	0
0	0	1.0000	-0.0655	0	0.4588
0	0	-0.0655	1.0000	0	0.4655
0.4635	0.4625	0	0	1.0000	0
0	0	0.4588	0.4655	0	1.0000

fx >>

### Statistical analysis: Design orthogonality



Measure : abs. value of cosine of angle between columns of design matrix  
Scale : black - colinear (cos=+1/-1)  
white - orthogonal (cos=0)  
gray - not orthogonal or colinear

# Review of Collinearity

**Rule of thumb: Correlations of 0.4 or greater are considered “moderate” (source: AFNI command xmat\_tool.py)**

**However, a high correlation between one set of regressors may not matter, given the regressors you are focused on**

**The challenge is to include as many regressors as is reasonable, without overfitting or introducing collinearity**

# Variance Inflation Factor

What what if one regressor is a linear sum of two or more other regressors? Pairwise correlations don't show this

e.g., does  $X_1 = X_2 + X_3$ ?

## Variance Inflation Factor

$$X_1 = \beta_0 + \beta_1 X_2 + \beta_2 X_3 + \epsilon$$

$$\mathbf{R} = \text{Cor}(X_1, \hat{\beta}_0 + \hat{\beta}_1 X_2 + \hat{\beta}_2 X_3) = \text{Cor}(X_1, \widehat{X}_1)$$



# Example

$X_1$	$X_2$	$X_3$
1	1	0
2	2	0
3	3	0
4	4	0
5	5	0
1	0	1
2	0	2
3	0	3
4	0	4
5	0	5

$$\text{cor}(X_1, X_2) = \text{cor}(X_1, X_3) = .39$$

$$X_1 = \beta_1 X_2 + \beta_2 X_3$$

What's the solution for the betas?

$$X_1 = \widehat{X}_1 \implies \text{cor}(X_1, \widehat{X}_1) = 1$$

## Example

$$VIF = \frac{1}{1 - R^2} = \frac{1}{1 - [\text{cor}(X_1, \widehat{X}_1)]^2}$$

**Goal: VIF < 5**

**What is a cutoff? VIF no greater than 10**

**Repeat the same process for each regressor in the model**

## VIF: Summary

Detects any collinearity from any combination of regressors

Matlab code: `vif = diag(inv(corrcoef(X)))'`;

Where “X” is the design matrix

# VIF: Summary

Useful for checking whether a design has high collinearity

Solutions: Remove the regressor, or change the design

These edits can be done before scanning


# Efficiency vs. Power

Two terms you will come across are Efficiency and Power

Let's begin with Power: Can you detect an effect  
if it is actually there?

As variance increases, power decreases

# Statistical Power



# Efficiency vs. Power

Efficiency is inversely proportional to variance

$$\frac{1}{c(X'X)^{-1}c'}$$

$$t = \frac{c(X'X)^{-1}X'Y}{\sqrt{\hat{\sigma}^2 c(X'X)^{-1}c'}}$$

$$\hat{\sigma}^2 = \frac{e'e}{N-p}$$

where  $e = Y - X\hat{\beta} = Y - \hat{Y}$

**All measures of efficiency are relative**

# Efficiency vs. Power


**Example: You have a fixed number of subjects that you can scan (due to budget, population, etc.)**

## **Options:**

- 1. Scan longer**
- 2. Include more trials**
- 3. Increase ITI**
- 4. Create a more efficient experiment**



# Efficiency vs. Power



# Efficiency vs. Power

Figure 2:  
Slow Event-Related Design -  
Fixed Inter-Stimulus Interval




Figure 3:  
Rapid Event-Related Design -  
Fixed ISI and Nonrandom Stimulus Presentation





Figure 4:  
Rapid Event-Related Design -  
Fixed ISI and Randomized Stimulus Presentation




# Estimation vs. Detection

**Detection is observing a signal if it is really there**

**Estimation is the analysis of the finer details of the signal, such as the shape of the BOLD response**

**There tends to be a tradeoff between the two**

# Fundamental Trade-off



# Optimization Strategies

**Let's say we just want to increase our efficiency;  
how to choose?**


**You could just create designs, calculate efficiency, and repeat**

**Drawbacks of this approach?**

# Optimization Strategies


## Permuted block design

Start with stimuli blocked and then randomly permute



# Optimization Strategies

## Genetic algorithm



# Optimization Strategies

## Resources

### Welcome to the Optseq Home Page

optseq2 is a tool for automatically scheduling events for rapid-presentation event-related (RPER) fMRI experiments (the schedule is the order and timing of events). Events in RPER are presented closely enough in time that their hemodynamic responses will overlap. This requires that the onset times of the events be jittered in order to remove the overlap from the estimate of the hemodynamic response. RPER is highly resistant to habituation, expectation, and set because the subject does not know when the next stimulus will appear or which stimulus type it will be. RPER is also more efficient than fixed-interval event related (FIER) because more stimuli can be presented within a given scanning interval at the cost of assuming that the overlap in the hemodynamic responses will be linear. In SPM parlance, RPER is referred to as 'stochastic design'.

The flexibility of RPER means that there are a huge number of possible schedules, and they are not equal. optseq2 randomly samples the space of possible schedules and returns the 'best' one, where the user can control the definition of 'best'. Cost functions include: average efficiency, average variance reduction factor (VRF), and a weighted combination of average and stddev of the VRF. The user can also specify that the first order counter-balancing of the sequence of stimuli be pre-optimized.

Download the [Linux version](#) of optseq2.

Download the [Linux x86\\_64 version](#) of optseq2.

Download the [MacOSX-PowerPC version](#) of optseq2.

Download the [MacOSX-Intel version](#) of optseq2.

Download the [Cygwin version](#) of optseq2.





# Optimization Strategies

```
(base) ajahn:~/Desktop/Flanker/2ndLevel_Inc-Con$ optseq2 --ntp 160 --tr 2 --psdwin 0 20 2
--ev disgustingPic 2 20 --ev attractivePic 2 15 --ev neutralPic 2 30 --evc 1 -1 0 --nkeep
3 --o IAPS --tnullmin 2 --tnullmax 8 --nsearch 1000
```

Why not just use  
the best one?

0.0000	2	2.000	1.0000	attractivePic
2.0000	0	2.000	1.0000	NULL
4.0000	2	2.000	1.0000	attractivePic
6.0000	0	2.000	1.0000	NULL
8.0000	1	2.000	1.0000	disgustingPic
10.0000	0	2.000	1.0000	NULL
12.0000	3	2.000	1.0000	neutralPic
14.0000	0	4.000	1.0000	NULL
18.0000	1	2.000	1.0000	disgustingPic
20.0000	0	2.000	1.0000	NULL
22.0000	3	2.000	1.0000	neutralPic
24.0000	0	2.000	1.0000	NULL
26.0000	1	2.000	1.0000	disgustingPic
28.0000	0	2.000	1.0000	NULL
30.0000	3	2.000	1.0000	neutralPic
32.0000	0	2.000	1.0000	NULL



# Optimization Strategies

## OptimizeX

TR you will use to acquire images →	TR (s):	<input type="text" value="1"/>
High-pass filter you will use to analyze images →	High-Pass Filter Cutoff (s):	<input type="text" value="128"/>
<b>Task Settings</b>		
# of conditions in your design →	N Conditions:	<input type="text" value="4"/>
# of trials per condition (unbalanced OK, e.g. 25 20 15 25) →	N Trials Per Condition:	<input type="text" value="20 20 20 20"/>
blocks = trials from same condition occurring in a row →	Maximum Block Size:	<input type="text" value="3"/>
<b>Timing (s)</b>		
duration of your trials (0 for purely event-related) →	Trial Duration:	<input type="text" value="3"/>
mean interstimulus interval →	Mean ISI:	<input type="text" value="3"/>
minimum value for interstimulus interval →	Min ISI:	<input type="text" value="2"/>
maximum value for interstimulus interval →	Max ISI:	<input type="text" value="6"/>
“rest” interval to add to beginning of scan →	Time before first trial:	<input type="text" value="10"/>
“rest” interval to add at end of scan →	Time after last trial:	<input type="text" value="10"/>
<b>Optimization Settings</b>		
number of “optimal” designs to save →	N Designs to Save:	<input type="text" value="5"/>
number of generations to test →	N Generations to Run:	<input type="text" value="50"/>
# of designs to include in each generation →	N Designs Per Generation:	<input type="text" value="1000"/>
maximum amount of time to run the program →	Max Time to Run (minutes):	<input type="text" value="2"/>
		<input type="button" value="Cancel"/> <input type="button" value="OK"/>

# Optimization Strategies

Settings

How many contrasts of interest?:

Cancel OK

This is me telling the software that I am looking for a design that maximizes the efficiency of two contrasts among my conditions.

Contrast Specification

Vector for Contrast 1:


Weight for Contrast 1:

Vector for Contrast 2:

Weight for Contrast 2:

Cancel OK

This is me telling the software that although I do care about the comparison among predictors 1 and 3 (**Contrast 1**), I actually care *more* about the comparison of predictors 2 and 4 (**Contrast 2**).



# Optimization Strategies

	A	B	C	D	E
1	Trial	Condition	Onset	Duration	ISI
2	1	3	10.00	3.00	4.77
3	2	1	17.77	3.00	7.32
4	3	2	28.10	3.00	6.03
5	4	4	37.13	3.00	5.20
6	5	1	45.33	3.00	4.04
7	6	4	52.37	3.00	6.31
8	7	3	61.68	3.00	2.69
9	8	2	67.37	3.00	4.92
10	9	3	75.29	3.00	4.45
11	10	1	82.74	3.00	2.13
12	11	3	87.88	3.00	2.04
13	12	2	92.91	3.00	2.87
14	13	2	98.78	3.00	2.56
15	14	4	104.35	3.00	2.59
16	15	4	109.93	3.00	3.53
17	16	3	116.46	3.00	4.43
18	17	1	123.88	3.00	3.10
19	18	1	129.99	3.00	4.77

# **Optimization Strategies: Summary**


**Each resource generates multiple designs**

**There is no best design; all efficiencies are relative!**

**Also need to consider whether the design “feels” right**

# Power Analysis

Remember this?



# Power Analysis

**Power analyses for behavioral studies are simpler:**

**Easier to recruit large N**

**Relatively inexpensive to run lots of subjects**

**Behavioral effects can be very strong**

# Power Analysis

**Now for imaging studies:**

**More difficult to recruit large N (e.g., >50 per study)**

**Expensive to run lots of subjects (\$500-\$900 per hour)**

**Imaging effects can be very weak**

**Several sources of noise**



# Power Analysis

What happens during grant writing?


Becomes a hunt for 80% power

Most fMRI studies won't have this kind of power,  
for the reasons listed above

Does that mean we shouldn't even do it in the first place?


# Power Analysis

What are reasonable ranges for power, given effect size?




# Power Analysis

What are reasonable ranges for power, given effect size?



# Power Analysis


What are reasonable ranges for power, given effect size?



# Power Analysis

What is the best way to estimate power?

Home > Education > Teaching Tools > G\*Power




## G\*Power for Mac

3.1.9.6

31 March 2020

Statistical power analysis program.

[Follow this app](#) [Developer website](#)




The screenshot shows the G\*Power software interface with the following parameters:

Input parameters	Output parameters
Test family: Statistical test	Noncentrality parameter $\delta$
Type of power analysis: A priori: Compute required sample size - given $\alpha$ , power, and effect size	Critical t
Effect size (d): 0.3	Df
$\alpha$ err prob: 0.05	Total sample size
Power (1 - $\beta$ err prob): 0.95	Actual power

# Power Analysis

Central and noncentral distributions Protocol of power analyses



critical t = 1.9876

Test family: t tests

Statistical test: Linear bivariate regression: One group, size of slope

Type of power analysis: A priori: Compute required sample size - given alpha, power, and effect size

Input parameters

Tail(s): Two

Determine

Slope H1: 0.1

alpha err prob: 0.05

Power (1-beta err prob): 0.8

Slope H0: 0

Std dev sigma\_x: 1

Std dev sigma\_y: 0.3464102

Output parameters

Noncentrality parameter delta: 2.8444520

Critical t: 1.9876083

Df: 87

Total sample size: 89

Actual power: 0.8031595

Input mode: p, residual sigma, sigma\_x => slope, sigma\_y

Correlation rho: 0.5

Std dev residual sigma: 0.3

Std dev sigma\_x: 1

Std dev sigma\_y: 0.3464102

Calculate

Slope H1: 0.1732051

Calculate and transfer to main window

Close effect size drawer

X-Y plot for a range of values Calculate

# Power Analysis

**What about estimating power from another published study?**

**Keep in mind that only significant results are usually published; this may just contribute to the file drawer problem (to be discussed more on Tuesday)**

# Power Analysis

What about calculating power after a study is run?  
(e.g., post-hoc power analysis?)

This is a statistical fallacy, since the null hypothesis has already been either rejected or not rejected; there is no “power” to calculate!



# Power Analysis

## Statistical Practice

---

### The Abuse of Power: The Pervasive Fallacy of Power Calculations for Data Analysis

John M. HOENIG and Dennis M. HEISEY

---

It is well known that statistical power calculations can be valuable in planning an experiment. There is also a large literature advocating that power calculations be made whenever one performs a statistical test of a hypothesis and one obtains a statistically nonsignificant result. Advocates of such post-experiment power calculations claim the calculations should be used to aid in the interpretation of the experimental results. This approach, which appears in various forms, is fundamentally flawed. We document that the problem is extensive and present arguments to demonstrate the flaw in the logic.

calculations as a matter of policy (Anon. 1995; Anon. 1998). We emphasize that these calculations are sought primarily with the thought that they are useful for explaining the observed data, rather than for the purpose of planning some future experiment. We even found statistical textbooks that illustrate the flawed approach (e.g., Rosner 1990; Winer, Brown, and Michels 1991; Zar 1996). Researchers need to be made aware of the shortcomings of power calculations as data analytic tools and taught more appropriate methodology.

It is important to understand the motivation of applied scientists for using power analysis to interpret hypothesis tests with nonsignificant results. The traditional, widely ac-

# Power Analysis


## Tools for power analysis

### Fmripower

#### What happened to the fmripower tool?

The fMRIPower tool hit old age and was starting to have quite a few issues. I have chosen to replace the tool with a set of instructions so you can carry out power analyses on your own. I will post that information soon! In a nutshell, all you really need to do is perform an ROI analysis, get your effect size and carry out a power analysis using that effect size. Of course, don't forget, you must use an a priori ROI. I realize it is super frustrating, but you cannot use the ROI that was active in the same data set from which you are running the power analysis.

Hopefully that's enough for now, but I will make a video and blog post with instructions soon.



The screenshot shows the homepage of the NeuroPowerTools website. At the top, there is a dark red navigation bar with the text "NeuroPowerTools", "NeuroPower" with a dropdown arrow, and "NeuroDesign" with a dropdown arrow. Below the navigation bar, the main content area is white. On the left side, there is a "Welcome" section with the following text: "During the design of an fMRI experiment, many parameters have to be decided prior to any data collection. Examples include: sample size, order of stimuli, timing of stimuli,... These parameters all have an effect on the outcome. A good design will optimise the balance between the power and the cost of the study. The results from a well planned design are more trustworthy and reproducible than any (pseudo-) random design." Below this, it says: "This website is a collection of small toolboxes to help design an fMRI study. NeuroPower helps deciding on the sample size, while NeuroDesign finds optimal order and spacing of stimuli." At the bottom of the welcome section, it states: "Everything happens online, so there's no need to download or install anything. Try it out now, or be sure to check back for our newest developments." On the right side of the page, there is a dark red silhouette of a human head in profile, facing left, with a white outline of a brain inside.

# Power Analysis

## Data location

Either paste a link to the online nifti-file OR upload your statistical map.

URL

Upload

Currently: [/maps/spmT\\_0001.nii](#)

Change:

No file chosen

## Mask location (optional)

Upload a full brain mask or a Region-of-Interest mask. If no mask is selected, all non-null voxels are used.

Maskfile

No file chosen

## Design specifications

Are the data Z- or T-values?\*

What is the screening threshold, also known as the clusterforming threshold or the excursion threshold (either p-value or z-value units)?\*

How many subjects does the group map represent?\*

Is this a one-sample or a two-sample test?\*

At which alpha-level are the statistical tests carried out?

Do you want to manually specify the smoothness or estimate from the data?

Note though that estimating smoothness on statistical maps leads to [biases](#). It is preferable to manually specify the data.\*

Manual

Estimate

What is the smoothness of the data in mm?

What is the voxel size in mm?

# Power Analysis

OVERVIEW START PEAK TABLE MODEL FIT **POWER CALCULATION** POWER TABLE RESET

There is not enough power to estimate a threshold for BH.

Power  Hover over the lines to see detailed power predictions

To see the power for a certain sample size or vice versa, please fill out either the minimal power or the sample size.


MCP\*

Random Field Theory ▾

Sample size

Power

Submit parameters



save svg

To obtain a statistical power of 0.8 this study would require a sample size of 41 subjects.

# Power Analysis

**When evaluating a power analysis, make sure that the estimates seem to fall within reasonable bounds, and that the parameters were clearly defined**

**Questions?**

# Group-Level Analysis

Once we have estimated a model for each individual subject (1<sup>st</sup>-level analysis), we combine them into a 2<sup>nd</sup>-level analysis

In SPM: Usually focus on just the mean of the parameter estimate; variance is discarded at the group level



## **Group-Level Analysis**

**N.B.: The way that betas are calculated in the 1<sup>st</sup>-level is different than how they are estimated at the 2<sup>nd</sup>-level**

**The difference can be expressed as “Fixed-Effects” vs.  
“Random-Effects”**

**Combining both generates “Mixed-Effects”**


# Group-Level Analysis



Fixed Effects



# Group-Level Analysis



# Group-Level Analysis



**Summary: Fixed Effects applies only to the subjects you sampled**

**Random effects assumes that the subjects were randomly sampled from the population, and that you're trying to make an inference about the population (i.e., parameters)**


**Mixed effects combines the two**

**Question: To reduce overall variance, should we collect more samples, or more subjects?**

# Group-Level Analysis



# Group-Level Analysis



# Group-Level Analysis

**Simplest model: 1-sample t-test**

**A parameter estimate (or contrast of parameter estimates, also called a contrast estimate) is submitted to a t-test**

**Is the average of the parameter (or contrast) estimates significantly different from zero?**

## **Group-Level Analysis**

**However, this typically isn't very interesting**

**Since fMRI signal is arbitrary, it is more useful  
to contrast one condition to another**

**You can then run a one-sample t-test on this contrast  
(to be discussed in a little bit)**


# Group-Level Analysis

e.g., button presses



# Group-Level Analysis


Very simple contrast (and useful to check whether your timings are correct!)






# Group-Level Analysis

What is this?



# Group-Level Analysis

How you specify the contrast weights depends on the order of the regressors




$$c = [-1 \ 1]$$

# Group-Level Analysis

In this example: Left was first, Right was second

How would I specify the contrast of Left-Right?



$$c = [-1 \ 1]$$

# Group-Level Analysis

In a group-level context

One-sample:

$$\begin{bmatrix} Y_1 \\ Y_2 \\ \vdots \\ Y_N \end{bmatrix} = \begin{bmatrix} \beta_0 \\ \beta_0 \\ \vdots \\ \beta_0 \end{bmatrix} + \epsilon$$

# Group-Level Analysis


In a group-level context

Two-sample:

$$\begin{bmatrix} Y_1 \\ Y_2 \\ Y_3 \\ Y_4 \\ Y_5 \\ Y_6 \end{bmatrix} = \begin{bmatrix} 1 & 0 \\ 1 & 0 \\ 1 & 0 \\ 0 & 1 \\ 0 & 1 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} \beta_1 \\ \beta_2 \end{bmatrix} + \epsilon$$

# Group-Level Analysis

## What about a paired t-test?



# Group-Level Analysis

What about an interaction?

If each subjects has two conditions (A,B) with two levels (1,2) then you can do the following contrast:

The image shows a software interface for defining a contrast. The dialog box is titled "define contrast..." and contains the following fields:

- name:** Interaction Contrast
- type:**  t-contrast  F-contrast
- contrast weights vector:** .5 -.5 -.5 .5

To the right of the dialog box is a visualization of the contrast matrix, labeled "contrast(s)". The x-axis represents the contrast weights (0, 0.2, 0.4, 0.6, 0.8, 1) and the y-axis represents the contrast values (0, 0.5, 1). The matrix shows a pattern of dark and light gray squares, indicating the contrast weights for each condition and level.

# Group-Level Analysis

What if we perform a one-sample t-test on contrasts?

e.g., calculate  $A-B$  for each of 10 subjects, to create 10 contrasts

Is this valid?



# Summary Statistics

The above is called a “summary statistics” approach

Valid if the intra-subject variabilities are relatively similar across subjects

For most studies, this assumption is true  
(Penny & Holmes, 2004)

# Summary Statistics

**Pros: Easy to implement, simplifies interactions**

**Cons: Assumptions may not be valid; check whether the variance and number of runs is similar for each subject**

**Example: Using Summary Statistics to run a one-sample t-test on an interaction term**



## Module List

Factorial design specification&lt;-

## Current Module: Factorial design specification

Help on: Factorial design specification

Directory	<-X
Design	
. Paired t-test	
.. Pairs	
... Pair	
... Scans [1,2]	<-X
... Pair	
... Scans [1,2]	<-X
... Pair	
... Scans [1,2]	<-X
... Pair	
... Scans [1,2]	<-X
... Pair	
... Scans [1,2]	<-X
.. Grand mean scaling	No
.. ANCOVA	No
Covariates	
Multiple covariates	
Masking	
. Threshold masking	

## Current Item: Scans [1,2]



Scans [1,2]

Select the pair of images.





## Module List

Factorial design specification&lt;-

## Current Module: Factorial design specification

Help on: Factorial design specification

Directory &lt;-X

Design

. One-sample t-test

. Scans &lt;-X

Covariates

Multiple covariates

Masking

. Threshold masking

. . None

. Implicit Mask Yes

. Explicit Mask

Global calculation

. Omit

Global normalisation

. Overall grand mean scaling

. . No

. Normalisation None

Enter Contrast estimates here

## Current Item: Scans

Specify...

## Scans

Select the images. They must all have the same image dimensions, orientation, voxel size etc.

# F-tests

Also called "omnibus" tests

Tests whether one or more contrasts is significant

Question: Does this maximize Detection or Estimation?

# F-tests

Instead of a contrast vector, F-tests require contrast matrices

*define contrast...*

*name*

*type*  t-contrast  F-contrast

*contrast*

contrast	1 0 0 0
weights	0 1 0 0
matrix	0 0 1 0

or eye(4)

or

columns for reduced design

contrast(s)

# F-tests

You can also specify multiple contrasts, e.g.:

$$\begin{bmatrix} 1 & -1 & 0 & 0 \\ -1 & 1 & 0 & 0 \\ 0 & 0 & 1 & -1 \\ 0 & 0 & -1 & 1 \\ 0 & 1 & -1 & 0 \\ 0 & -1 & 1 & 0 \end{bmatrix}$$

# Demonstration of Group-Level Analysis



# Correcting for Multiple Comparisons

**COMING SOON!**

# BLUE-EMU®

## Pain Relief *Micro-Foam*

**SOFT AND SMOOTH**

- 🌿 Skin Nourishing Pain Relief
- 🌿 Enriched with Aloe-vera
- 🌿 Advanced Micro-Foam™

AMERICA'S #1 EMU OIL FORMULA  
ODOR FREE


# BLUE-EMU®

America's Number One  
Emu Oil Formula



The Blue-Emu® product line is the #1 selling over-the-counter emu oil brand in the United States. Our products, loved by both customers and Hall of Famers like Rusty Wallace and Johnny Bench, are made with soothing Aloe Vera and penetrating Emu Oil right here in the USA. Our products allow you to get back in the game without smelling like a locker room.

Our product line includes Original Blue Emu® cream, Blue-Emu® Continuous Pain Relief Spray, Blue-Emu® Maximum Arthritis Pain Relief Cream, and Blue-Emu® Maximum Strength Lidocaine Numbing Pain Relief Cream. You can feel 100% confident in using our products to help soothe tired muscles and joints.

# Correcting for Multiple Comparisons



# Correcting for Multiple Comparisons




# Correcting for Multiple Comparisons


Now consider an fMRI dataset

Quick poll: How many voxels in a typical volume?

Depends on voxel size, but usually between 100k-300k



Test for significance in each voxel



# Correcting for Multiple Comparisons

Balancing act between Type I and Type II errors


## Legal Errors

		Actual Criminal	
		Yes Alternate Hypo	No Null Hypothesis
Decision on the basis of Case Trial	Punish (Criminal)	Good Decision	Convicting the Innocent
	Acquit (Innocent)	Acquit Guilty	Good Decision




# Correcting for Multiple Comparisons


High Threshold



Med. Threshold



Low Threshold



Good Specificity

Poor Power

(risk of false negatives)

Poor Specificity  
(risk of false positives)

Good Power

# Correcting for Multiple Comparisons

What can be done?

**Bonferroni correction**

**FDR correction**

**Cluster correction**



# Bonferroni Correction



Simplest correction method to understand and calculate

Given an alpha level  $\alpha$  and number of tests  $n$ ,  
the corrected alpha level can be found by  $\alpha/n$

Example:  $\alpha=0.05$ ,  $n=10$

$$\alpha = 0.005$$

# Bonferroni Correction



# Bonferroni Correction

Example:  $\alpha=0.05$ ,  $n=100,000$

$$\alpha = 0.000005 (!)$$

This revised alpha is then used at each voxel in the analysis

# Bonferroni Correction

**Pros: Easy to understand, easy to use**

**Excellent for guarding against Type I error**

**Cons: Conservative, too severe for fMRI**

**Inflates the probability of Type II errors**

## **Alternative: False Discovery Rate (FDR)**

**Bonferroni and other correction methods control for the Probability of observing a single false positive**

**FDR: Control the fraction of false positives**

**i.e.: You know there will be a certain percentage of false positives, but you can live with it**

# Alternative: False Discovery Rate (FDR)

- FDR


- E (# of true null declared active / # voxels declared active)

---


	Declared active	Fail to Declare active	Total
Non-active	50	950	1000
Active	80	20	100
Total	130	970	1100

---


Noise




Signal



Signal+Noise




## Control of Per Comparison Rate at 10%



11.3% 11.3% 12.5% 10.8% 11.5% 10.0% 10.7% 11.2% 10.2% 9.5%

Percentage of Null Pixels that are False Positives


## Control of Familywise Error Rate at 10%



FWE

Occurrence of Familywise Error

## Control of False Discovery Rate at 10%



6.7% 10.4% 14.9% 9.3% 16.2% 13.8% 14.0% 10.5% 12.2% 8.7%

Percentage of Activated Pixels that are False Positives




# Cluster Correction

**Bonferroni might be appropriate if each voxel were independent**

**But are they? Consider how the brain is designed**


# Cluster Correction

Functional image, unsmoothed



# Cluster Correction

Functional image, smoothed



# Cluster Correction

In SPM, cluster correction thresholds are calculated with  
Random Field Theory (RFT)

Accounts for the spatial smoothness of the data

Based on the estimated FWHM<sub>x</sub> (not the same as  
applied FWHM<sub>x</sub>!)

# Cluster Correction

## Example after 8mm smoothing kernel

*table shows 3 local maxima more than 8.0mm apart*

---

Height threshold:  $T = 2.34$ ,  $p = 0.010$  (1.000)  
Extent threshold:  $k = 30$  voxels,  $p = 0.107$  (0.999)  
Expected voxels per cluster,  $\langle k \rangle = 11.965$   
Expected number of clusters,  $\langle c \rangle = 7.21$   
FWEp: 4.869, FDRp: Inf, FWEc: 198, FDRc: 198

Degrees of freedom = [1.0, 278.0]  
FWHM = 10.5 10.5 10.2 mm mm mm; 3.5 3.5 3.4 {voxels}  
Volume: 1811403 = 67089 voxels = 1431.6 resels  
Voxel size: 3.0 3.0 3.0 mm mm mm; (resel = 41.85 voxels)

# Cluster Correction

Statistics: *p-values adjusted for search volume*

set-level		cluster-level			
$p$	$c$	$p_{\text{FWE-corr}}$	$q_{\text{FDR-corr}}$	$k_E$	$p_{\text{uncorr}}$
0.846	5	0.026	0.024	198	0.000
		0.537	0.175	85	0.011
		0.999	0.794	31	0.102
		0.489	0.175	89	0.010
		0.105	0.050	146	0.002

# Multiple Comparisons Correction: Summary


Most common method is cluster-wise thresholding

Cons: Loss of spatial specificity

As we will see tomorrow, you should use a  
Cluster-forming threshold of  $p=0.001$  for most experiments

Non-parametric options seem to be getting more popular

# Applying this to a dataset





# Applying this to a dataset

**Set-level: Probability of finding that many clusters**

**Cluster-level: Probability of finding a cluster of a given size**

**Peak-level: Probability of a statistic that size in that voxel**

# Applying this to a dataset

Statistics: *p-values adjusted for search volume*

set-level		cluster-level				peak-level					mm	mm	mm
$p$	$c$	$p_{\text{FWE-corr}}$	$q_{\text{FDR-corr}}$	$k_E$	$p_{\text{uncorr}}$	$p_{\text{FWE-corr}}$	$q_{\text{FDR-corr}}$	$T$	$(Z_E)$	$p_{\text{uncorr}}$			
0.846	5	0.026	0.024	198	0.000	0.716	0.996	4.00	3.94	0.000	-39	-73	-22
						1.000	0.996	3.26	3.23	0.001	-42	-52	-19
						1.000	0.996	3.24	3.20	0.001	-27	-70	-16
		0.537	0.175	85	0.011	0.912	0.996	3.79	3.74	0.000	42	-40	-19
						1.000	0.996	3.12	3.09	0.001	48	-52	-25
						0.999	0.794	31	0.102	0.998	0.996	3.48	3.44
		0.489	0.175	89	0.010	1.000	0.996	3.26	3.22	0.001	24	-1	65
						1.000	0.996	2.91	2.89	0.002	33	2	50
						1.000	0.996	2.89	2.86	0.002	30	-7	50
						0.105	0.050	146	0.002	1.000	0.996	3.24	3.20
1.000	0.996	3.11	3.08	0.001	0	29	26						
					1.000	0.996	3.04	3.01	0.001	-3	20	71	

# Demonstration

## **Other Statistical Scenarios**

**Once you calculate a contrast, are you done?**

**Consider this: My brother and I both play basketball. If I tell you that I am slightly better than he is, does that mean:**

**We are both really good, but I'm just a little better?**

**I'm a little above average, and he's a little below average?**

**Maybe we're both terrible, and I'm just a little better than he is**




# Double Dissociations


**Condition A is significant in region A but not region B, and condition B is significant in region B but not region A**

**Remember to run a paired t-test within each region,  
and also a Region x Condition interaction**

# Double Dissociations




# Double Dissociations





# Triple Dissociations (!)



## **Preview: ROI Analysis**

**In the examples just shown, the data was extracted from  
Regions of Interest (ROIs)**

**That is, subsets of voxels that we are interested in**

HUMAN ATLAS->TD brodmann areas+

- ..
- brodmann area 1
- brodmann area 2
- brodmann area 3
- brodmann area 4
- brodmann area 5
- brodmann area 6
- brodmann area 7
- brodmann area 8
- brodmann area 9
- brodmann area 10
- brodmann area 11
- brodmann area 12
- brodmann area 13
- brodmann area 14
- brodmann area 15
- brodmann area 16
- brodmann area 17
- brodmann area 18
- brodmann area 19
- brodmann area 20
- brodmann area 21
- brodmann area 22
- brodmann area 23
- brodmann area 24
- brodmann area 25
- brodmann area 26
- brodmann area 27
- brodmann area 28
- brodmann area 29
- brodmann area 30
- brodmann area 31
- brodmann area 32
- brodmann area 33
- brodmann area 34
- brodmann area 35
- brodmann area 36
- brodmann area 37
- brodmann area 38
- brodmann area 39
- brodmann area 40
- brodmann area 41
- brodmann area 42
- brodmann area 43
- brodmann area 44
- brodmann area 45
- brodmann area 46
- brodmann area 47
- Amygdala
- Anterior Commissure
- Caudate Body
- Caudate Head

Atlas Information

BASIC    ADVANCED

ADD ->

MOVE ALL ->>

<- REMOVE SELECTED

<<- REMOVE ALL


2D    3D

DILATE:    1

Flip Lock     L/R     U/D

Left    Left + Right    Right

Display: Neurologic    49



L    R

ITKSnap

Mag

ANALYSIS    RESULTS

Write Independent Regions




SAVE MASK

DONE    CANCEL

WORKING REGION1

brodmann area 32

	CUBE	46	64	37	GO	ATLAS	SUBREGION	VALUE
MNI		0	0	0	GO	TD brodmann areas+	NA	1000
Tal		0	0	0	GO	TD Lobes	NA	1500



1: dACC\_Sphere

Label: dACC\_Sphere

Centre of mass: 0 20 40

Volume (mm): 648.00

Max/min X(mm): -4 4

Max/min Y(mm): 16 24

Max/min Z(mm): 36 44

**Questions?**

# Lab Preview

Create an ideal experimental design, *before* collecting data

For AFNI users: Similar to using the `-nodata` option  
in `3dDeconvolve`, calculating correlations


Parameters to change: ISI, number of trials, and contrasts

# Lab Preview

```
ts = output.X0;           % get the raw timeseries from 'output'  
tr = output.TR;          % do the same for the TR  
irf = spm_hrf(tr);       % create the impulse response function  
cts = conv(ts, irf);     % convolve the timeseries with the IRF  
cts = cts(1:length(ts)); % ensure that the long tail of the hemodynamic response hasn't  
lengthened our image timeseries
```

# Lab Preview

Using OptimizeX to specify which contrasts you are interested in



A dialog box titled "Contrast Specification" with a standard macOS window title bar (red, yellow, and grey buttons). The dialog contains four input fields for specifying contrasts. The first two fields are for Contrast 1, and the next two are for Contrast 2. The "Weight for Contrast 2" field is currently selected with a blue border. At the bottom, there are "Cancel" and "OK" buttons.

Vector for Contrast 1:	1 0 -1 0
Weight for Contrast 1:	1
Vector for Contrast 2:	0 1 0 -1
Weight for Contrast 2:	2

Buttons: Cancel, OK



# Lab Preview

Create several design matrices, calculate VIF

We will provide the code for this

# Lab Preview

## Exploring the SPM.mat file

### details on experiment:

SPM.xY.RT - TR length (RT ="repeat time")

SPM.xY.P - matrix of file names

SPM.xY.VY - # of runs x 1 struct array of mapped image volumes (.img file info)

SPM.modality - the data you're using (PET, FMRI, EEG)

SPM.stats.[modality].UFp - critical F-threshold for selecting voxels over which the non-sphericity is estimated (if required) [default: 0.001]

SPM. stats.maxres - maximum number of residual images for smoothness estimation

SPM. stats.maxmem - maximum amount of data processed at a time (in bytes)

SPM.SPMid - version of SPM used

SPM.swd - directory for SPM.mat and img files. default is pwd

### basis function:

SPM.xBF.name - name of basis function

SPM.xBF.length - length in seconds of basis

SPM.xBF.order - order of basis set

SPM.xBF.T - number of subdivisions of TR

SPM.xBF.T0 - first time bin (see slice timing)

SPM.xBF.UNITS - options: 'scans'!'secs' for onsets

SPM.xBF.Volterra - order of convolution

SPM.xBF.dt - length of time bin in seconds

SPM.xBF.bf - basis set matrix